

Model 2R63



Save time, labor, and money with a complete turn-key solution for your baling needs.

The 2R63 two-ram, auto-tie baler chassis utilizes the same interlocking designs found in larger EXCEL® two-rams while remaining very economical. The 2R63 is constructed of four solid steel sheets (top, bottom, and both sides), providing seamless construction from

end to end. Combine this innovative engineering with our use of only the highest quality components, and the result is the very best in durability and function.

- **No Fluffing!**
- **No Shredding!**
- **No Tying!**

The EXCEL® Model 2R63 bales the following materials:

Office Paper, Newspaper, OCC, magazines, PET, HDPE, Aluminum Cans, Tin Cans, Printer's Waste, and other Materials

Standard Features Include

- The 2R63 is manufactured standard with either left-hand or right-hand eject
- U.S. Wire Tie Systems Automatic 13 Gauge Wire Tier, Model 343
- 20HP TEFC Motor, Standard Voltage - 208, 230, 460 Volt, 60 Hertz, 3 Phase
- Horsepower Limited Pressure Compensated Piston Pump
- 29 Second Main Ram Dry Cycle Time
- Short Stroke Selector Reduces Cycle Time to 21 Seconds
- Remote Operating Controls Mounted on Pedestal
- Percent of Bale Complete Indicator Lights
- Automatic Bale Sizing System
- Automatic Shear Jam Correction
- EXCEL's® 1-2-3 Limited Warranty (1 Year Labor, 2 Years Parts, 3 Years Structural and Cylinder) (U.S.A. Only)
- Full Platen Penetration
- Complete with MV32 Hydraulic Oil
- NEMA 12 rated Enclosures and Controls
- Power Unit Mounted on back of the Machine for Space Savings
- Air/Oil Heat Exchanger
- One Spool of 13 Gauge Ultra Tensile Galvanized Wire
- Sandblasted, Primed, and Painted Excel Blue for Long Lasting Durability
- Standard Hopper
- Lower Photo Eye
- UL, CUL Approved (CE Available)
- Available with an EXCEL® above ground or in-ground conveyor for a turn-key system
- Tongue and Groove Floor Liner Standard